REF: 48 BM OP 4 LGX

Fiber metal wall box for 4 LGX modules

P/N : 48BMOP4LGX (shown partially loaded)

48MODLGXS8LCD

48MODLGXS8SCS

21 LGX modules available on request

Applications

The fiber metal wall box range can be used as a demarcation point or a sub-distribution unit for riser links. It is delivered unloaded, ready to receive a various range of LGX modules.

General Characteristics

- Metal wall box for 4 LGX module adapter plates.
- Receives up to 96 fibers, ST, FC, SC, LC, MTRJ or E2000, multimode or singlemode
- Including cable management rings for bending radius protection
- Suitable for indoor applications only
- Multiple cable entry possibilities : 4 x through cable glands on top, 4 on bottom

Physical properties

- Cold rolled steel 12/10mm
- Electro Static Powder coating light grey RAL 7035 (RAL 7016 as an option on request)
- IP 20
- Operating temperature : -40°C to + 60°C
- 4 x 20mm cable entries
- 4 x 25mm cable entries
- Locking system including a key
- Dimensions :
  - Width 360 mm x depth 120 mm x height 360 mm
  - Width when the door is open : 452 mm
- Weight : 7.5 kg

This document is confidential, and is the property of Multimedia Connect. Multimedia Connect own the copyright, and the document must not be copied or changed in any form, wholly or in part without written permission from Multimedia Connect. The contents of this document must be disclosed to any other person or persons.
The characteristics related to this document are not contractual, and can be modified without warning.

REF: 48 BM OP 4 LGX

Fiber metal wall box for 4 LGX modules

Related products

	LGX adapter plate modules	Packing
Part numbers structure	48 MOD LGX **w** **x** **yyyyy**	Unit
Replace **w** by the type of fiber	S for singlemode, M for multimode	
Replace **x** by the number of adapters	6 for duplex SC, Quad LC	
	8 for ST, SC, FC, duplex LC, MTRJ, E2000	
Replace **yyyy** by the type of adapters	ST, FC, SC, SCD, LCD, MTRJ, MTP SCS-APC, SCD-APC, FC-APC, LCD-APC LC Quad, LC Quad APC, E2000, E2000-APC	
48 MOD LGX OB	Blank LGX adapter plate	Unit

48MODLGXS8ST

48MODLGXM8MTP

48MODLGXS6SCAPCD

Standards

Tested to comply with the requirements of :

- TIA/EIA 568 C.3,
- ISO/IEC 11801 Amd 1.0/ Amd 2.0,
- EN 50173, EN 297-1
- IEC 60304, IEC 61754
- ROHS, REACH, SvHC

Ordering Information

Part numbers	Description	Packaging
48 BM OP 4 LGX	Fiber metal wall box for 4 LGX modules	Unit

This document is confidential, and is the property of Multimedia Connect. Multimedia Connect own the copyright, and the document must not be copied or changed in any form, wholly or in part without written permission from Multimedia Connect. The contents of this document must be disclosed to any other person or persons.
The characteristics related to this document are not contractual, and can be modified without warning.